

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV = AS/EN/JISQ 9100 = COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV = ISO 9001 =





TECHNICAL DATA SHEET

PRODUCT EMI Shielding Film

CODE 16.10343-A0

P/N VS.12000.XXXX.0,20.PET.ITO.NA.NA

DESCRIPTION SOLEMI ITO FILM

Thickness: 0,20mm Width: 1200mm Adhesive: NO PSA Supply method: Roll



MATERIAL SPECIFICATIONS


Material code: 16.10343-A0 - VS.12000.XXXX.0,20.PET.ITO.NA.NA

DAIA	VALUE
DESCRIPTION	EMI Shielding Film with one side ITO and the other side plastic
COATING	ITO treatment
THERMAL STABILITY [(r-r0)/r0]	< ± 15%
WET RESISTANCE [(r-r0)/r0]	< ± 15%
LOW-TEMPERATURE RESISTANCE [(r-r0)/r0]	< ± 15%
TRANSPARENCY [%]	from 76 to 81

SURFACE RESISTANCE [Ohm]
SHIELDING EFFECTIVENESS

SHIELDING EFFECTIVENESS 10 kHz - 40 GHz)

 5.0 ± 1.0



Frequency (kHz - GHz)

STORAGE CONDITION

It should be stored indoors at a temperature between 15°C and 35°C and a relative humidity of less than 80%

These values are measured under laboratory conditions. Results may vary in other situations; please read our Guarantee.