


Data Sheet
Conductive fabric - SC.NI

Name STATIC CLEAN- SC.NI

Description Nickel coated fabric



Type of raw material Polyester fabric

Thickness (mm) 0.25 +/- 0.07

Max Surface resistivity (Ohm/sq) 0,4

Temperature range (°C) -40 to 90

Maximum weight (g/mq) 165

Flammability rating NA

Typical shielding effectiveness 85 dB from 1 MHz to 100 MHz

60 dB from 100 MHz to 1 GHz

Additional coating NA

Product applications Base material for room shielding, base material for EMI/RFI

Safety Data The product is considered "article" according to REACH (Reg. 1907/2006), so it's not subject neither to the obligation of safety data sheet, nor of Classification and Labelling according to Reg 1272/2008 (CLP). Use gloves to handle and avoid contact with irritated or injured skin